



## FloPlast Hollow Soffit Board

### G20/950

FloPlast Hollow Soffit Board is 10 mm thick with a tongue and groove profile of a hollow cell construction, manufactured from PVC-U.

Boards are available in 300 mm width.

All boards are supplied in 5.0 m lengths.

FloPlast PVC-U products have been tested in accordance with BS 476:7 1997 and have a Class 1Y fire rating. Consult FloPlast Ltd technical literature for details. FloPlast Ltd can also provide a design and specification service and it is recommended that they are consulted early in the design process.

**Manufacturer:** FloPlast Ltd. Castle Road, Eurolink Business Park, Sittingbourne. Kent. ME10 3FP.  
Tel: 01795 431731. Fax: 01795 431188. Email: [technical@floplast.co.uk](mailto:technical@floplast.co.uk) Web: [www.floplast.co.uk](http://www.floplast.co.uk)

**Product reference:** FloPlast Hollow Soffit  
300 mm ref: H300.

**Thickness:** 10mm (nominal)

**Finish:** Smooth semi-matt

**Colour:** White. Foiled woodgrain Golden Oak, Black Ash, Rosewood & Anthracite Grey

**Accessories:** Trim Ref: HJ

Trim Ref: HH

**Fixing:** Recommended method of fixing is A4 stainless steel cladding pins, 30 mm long, with 2.0 mm shank. Consult with FloPlast for recommendations and details.

**Approvals:** Organisation: British Board of Agrément  
Certificate: No 00/3771