



FloPlast Vented Soffit Board

G20/900

The cellular boards comprise a closed cell cellular PVC-UE core beneath an outer weathering impact modified PVC-U skin and have a vented area of 12500 mm² per metre run (equivalent to a continuous vent 12.5 mm wide at eaves)..

FloPlast PVC-U products have been tested in accordance with BS 476:7 1997 and have a Class 2Y fire rating.

A full range of injection moulded trims is available to suit FloPlast PVC-U Boards.

Consult FloPlast Ltd technical literature for details. FloPlast Ltd can also provide a design and specification service and it is recommended that they are consulted early in the design process.

Manufacturer: FloPlast Ltd. Castle Road, Eurolink Business Park, Sittingbourne. Kent. ME10 3FP.
Tel: 01795 431731. Fax: 01795 431188. Email: technical@floplast.co.uk Web: www.floplast.co.uk

Product reference: FloPlast Vented Soffit Boards

100 mm wide Ref: V100
150 mm wide Ref: V150
175 mm wide Ref: V175
200 mm wide Ref: V200
225 mm wide Ref: V225
250 mm wide Ref: V250
300 mm wide Ref: V300
404 mm wide Ref: V404

Thickness: 10mm (nominal)

Finish: Smooth semi-matt

Colour: White. Foiled Golden Oak, Black Ash, Rosewood and Anthracite Grey.

Accessories: In-line Jointing Trim Ref: RT20
Edge Capping Trim Ref: RT21. - White only.

Options: 175mm, 200mm, 250mm, 304mm and 404mm are available double vented with an equivalent continuous eaves airway of 25mm. Special order only

Fixing: Recommended method of fixing is A4 stainless steel nails 40mm long 2.0 mm shank.
Consult with FloPlast for recommendations and details.

Approvals: Organisation: British Board of Agrément
Certificate: No 00/3771